

## C3 Series Firmware Feature Matrix

Firmware Version		Standalone (K301)	All round (K304)	Advanced (K306)
Function Keys (~)	Hold	Manual	+Peak	+Peak
	Counting	-	S	S
	Auto Tare	-	S	S
	Totalising	-	S	S
	Display Test	S	S	S
	High Res (x10)	S	S	S
Quick Calibration		S	S	S
Units Switching lb/ kg/ oz/ g / t/ TN/ lb:oz/custom (switching between up to <b>three</b> units plus counting)		S	S	S
Multiple Tare (enhanced)		S	S	S
Medical hold		-	S	S
Multi color backlight		-	S	S
QA Date		-	S	S
mV/V Calibration		-	S	S
Clock Calendar		-	S	S
Remote Inputs		-	2	2
Isolated Outputs		-	2	2
Custom AUTO/SINGLE Output		S	S	S
Ring Network rinCMD		A	S	S
SIMPLE Network emulation		-	S	S
Printing		-	Programmable	
RS232 onboard		-	2	2
Extra Serial Port – Card (#) RS232, RS485, 20mA LOOP		A	A	A
Livestock Weighing		S	S	S
Gravity Compensation		S	S	S
Linearisation		S	S	S
Mimic Mode		-	S	S
Check Weighing (RGB Backlight)		-	S	S
Set Points		-	Basic (8)	Adv (8)
Alibi WELMEC 7.2 (DSD)		-	S	S
Programmable DSD CSV Log (#)		-	-	S
Bluetooth/WIFI (*)		A	A	A
Li-ion battery (*)		A	A	A
Analogue Expansion Card (*)		-	-	A

S – Standard Accessory

A – Optional Accessory

(\*) – Accessory under development

# – Readable via the registers

(~) – 2 functions supported simultaneously in US version with dedicated unit switching &amp; 3 functions supported simultaneously in ROW version