













Rinstrum Indicator Comparison

Model	# 350 Ohm Load cells	Ingress Protection	Function Inputs	Set Points	Inputs/Outputs	RS232 Ports	RS485 Ports	Networking	Custom Calendar	Custom Printing	Software	Unit Switching	Dual Range %	Check Weigh Bands	Hold & Peak Hold	Totalising Printing	Report Printing	Counting	Logic Setpoints	Batching (stages)	Speeds for Fill	Materials	Modbus ASCII	Modbus TCP	Ethernet/IP	Tilt Compensation	Date Storage	Ethernet TCP	LIA Scripting	Sum Master/Slave	Truck Weighing	Bluetooth Serial	Bluetooth Slave	Approvals							
 C357		IP67		3 7	- Basic (8) Adv (8)	- 4 in 4 out	- 2				S S**	K301 K304 K306 (A)	-		- 3	Manual Manual + Peak	- S	- S	- S																5	Advanced All Round Standalone					
 C350		IP66	8	3 7	- Basic (8) Adv (8)	- 4 in 4 out	- 2	A	S A		S S**	K301 K304 K306 (A)	S	S***	1	- 3	Manual Manual + Peak	- S	- S														(A)	5	Standalone All Round Advanced Standalone						
 C320		IP65 aa		3 5	- Basic (8) Adv (8)	- 2 in 2 out	- 2				S S**	K301 K304 K306 (A)	-		- 3	Manual Manual + Peak	- S	- S															5	Advanced All Round Advanced							
 C520		IP65 aa	11					S A	S A																																
 C527		IP65	16		Adv (8)	A 8 I/O		S A	S A		S*	K501	A	S	S	1	-	S	-	S	S					S	S	A	S	-	S	A	S	-	A	1,2,5	Process Control Truck Weighing				
 C530		IP30	8					A	A																																
 R420		IP65 aa	16	8				S A	S# A	S A	S	S**	K401 K402 K404 K405	A A	S S	S S	250 -	- -	S -	S S	S S	S S																			
 R423		IP66 aa	8	8		A 32 I/O		S A	S# A	S A	S	S**	K410 K411 K412	A A	- S	S S	100 -	- -	- -	S S	S S	S S	10 10	1 6	3 3																
 R427		IP66	-										K422 K491 K481	- A	S S	S S	250 250	- -	S -	S S	S S	S S																			
 R320/ R323		IP65 aa	4~	1		1 in 1 in 2 out		S	A^	S		S*	K342 K344 K346 K354 K356 K356-C1 K356-C2 K356-C3 K356-C4	- -	S -	- -																									
 X320		IP69K IP68	4~	1		3 Out 1 In		S	A^	S	S	S*	K376 K376-LIVE	- -	S -	- -	1 -	3 -	C Manual	C -	S -	S -																			
 1203-D		IP65	6	1	2	2 Out 1 In		S	S	S																															

^ Convert RS232 port to RS485 with a 0080
 # Transmit only
 ~ 8x350ohm for non trade
 % R400 Series Indicators are dual range & dual interval
 aa Indicators achieve this IP ratings from the front only when correctly panel mounted
 ^ Basic Over/ Under Setpoints
 ^^ Advanced Set Points
 * Custom printing
 ** Advance custom printing
 *** triple range

S Standard
 A Accessory or Option
 (A) Accessory or Option exclude e
 ## Bluetooth & wifi
 C – Cross Grade
 C1 – K356-PEAK (R300-572)
 C2 – K356-LIVE (R300-573)
 C3 – K356-COUNT (R300-574)
 C4 – K356-MED (R300-575)
 Approvals 1 NMI Australia
 2 OIML R76
 3 New Zealand
 4 NMI S1/O/B
 5 NTEP (III/III L)